## LIGHTING KIT

### KIT LTG-1800 NSN: 5180-01-587-7804



#### Universal Power Conditioner/Converter & Multiple Battery Charger

#### **Features:**

- Plug-Ins Can Charge 12 Batteries at Once (Solar Panel Charges Two 3-Battery Bags at a Time)
- Batteries Charge in Less than 8 Hours, and Maintain a Full Charge While Connected to a Power Source
- Automatic Shut-Off When Charge is Complete, Complete, Storage Box May Remain Closed During Charging Process
- Impact Resistant, Water-Resistant
   Case on Wheels for Easy Transportation





2 Solar Panels w/ 2.5' Pig Tail



Wearable High Capacity Battery Pack



24 Volt DC/Nato Slave Plug w/ 10' Pig Tail



(12) 18V XR+ Battery Packs 2.4 AMP Hour



<sup>\*</sup> All prices subject to change based upon addition of new components. Components may be substituted due to availability. Items may not be shown individual.

## LIGHTING KIT

## KIT LTG-1800

NSN: 5180-01-587-7804



(2) Pivoting **Spot Light** 



**Customizable Electronics for Many Voltage or Current Requirements.** 



**All Weatherproof** Weight 130 lbs. Dimensions - 22"H x 32"W x 20"D



#### **Various Interconnect Cables Available**









110 Volt AC w/ 10' Pig Tail 12 Volt DC w/ 10' Pig Tail Clamp-On Terminal Adapter (2) Pig Tail

\* All prices subject to change based upon addition of new components. Components may be substituted due to availability. Items may not be shown individual.



### The Power Of Choice Super Quiet Inverter Generators

Honda's advanced technology makes these generators extremely **lightweight**, **portable** and **fuel-efficient**. Honda's Inverter Technology creates "clean" or stable power – making these generators ideal for sensitive electronic equipment. And since they are totally enclosed, they are incredibly **quiet**.

All models feature Honda's easy-starting, reliable, OHV horizontal shaft, GXH, mini 4-stroke engine, which meets EPA and CARB emission standards.

The Eco-Throttle system incorporates a load-dependent speed control-type governor that offers excellent fuel economy by automatically adjusting engine speed to the optimum level, given the usage load.



#### HON EU1000i

- ▶ 120V, 1000W Max (8.3A) AC Output
- ▶ 3.8 hrs of runtime on one tank @ rated load



### HON EU2000i

- ▶ 120V, 2000W Max (16.7A) AC Output
- ▶ 4 hrs of runtime on one tank @ rated load



#### HON EU3000is

- ▶ 120V, 3000W Max (25A) AC Output
- ▶ 7.2 hrs of runtime on one tank @ rated load



\* All prices subject to change based upon addition of new components. Components may be substituted due to availability. Items may not be shown individual.



# Megger.



#### M7029

**Dual-Display Multimeter** 

- Dual-Display offers simultaneous readings of six different pairs of measurements, plus analog bar graph
- 1000 V DC/750 V AC
- 10 Amps AC/DC 40 MU



#### PMM-1

Power Multimeter Multi-function Measuring Instrument

- Simultaneous measurement & display of all three-phase system parameters
- Accurate phase angle measurement at low current levels
- Versatile, menu-driven instrument with a built-in timer & data logging



10kV Insulation Tester

- Operates from mains or rechargeable supply
- Real-time data output and on-board storage for subsequent download
- Results displayed as insulation resistance or leakage current
- Integral timer for automatic insulation resistance & polarization index tests
- Integral lead storage



OTS60SX

Semi Automatic Oil Test Set

- Lightweight oil di-electric strangth test
- Suitable for field use & can be powered from a range of mains supplies
- Output Voltage: 0-60 kV
- Display: LCD
- Rechargeable battery: 12V, 12-Ah



#### 212159

Insulation Resistance Tester

- Test voltage (V DC) 100, 250, 500, 1000
- Insulation resistance 0 to 2000 MU
- Resistance Range 0 to 5000 MU
- · Hand-cranked power source
- Analog display
- \* All prices subject to change based upon addition of new components. Components may be substituted due to availability. Items may not be shown individual.





## Battery Service Equipment Set

### **KIT BSES-R** NSN 5180-01-590-6830







RediPulse Pro-12 Multiple **Battery Charge System** PUL 746X912



MDX-490PT



